

SERVO Servo spiral bevel gearboxes

VOGEL servo spiral gearboxes are ideal for maximum demands on dynamics. The sturdy and durable power packs are flexible to use and can be installed in any position thanks to a flexible lubricant system. Like all VOGEL spiral bevel gearboxes, they are manufactured using the modern production method of ground circular arc teeth according to Klingelnberg. For customers, this means greater toothing quality and precision as well as even faster delivery times.



SK

Angular gearbox with solid shaft without key

Ratios:	i	[-]	3,0 - 10,0
Max. acceleration torque:	$T_{2\maxzul}$	[Nm]	54 - 217
Nominal torque on output shaft:	T_{2Nzul}	[Nm]	40 - 150
Max. backlash:	j	[arcmin]	2 - 5
Max. input speed:	$N_{1\maxzul}$	[min ⁻¹]	6500 - 7500

The operating mode is S5. Please contact us if you intend to use other operating modes.

[Catalogues and maintenance instructions](#)

[2D and 3D data](#)

[Inquiry form](#)

Do you have individual requirements?

We have the right customer-specific solution for you. We look forward to hearing from you.

[Customized solution](#)



SKH

Angular gearbox with hollow shaft with shrink disc

Ratios:	i	[-]	3,0 - 10,0
Max. acceleration torque:	$T_{2maxzul}$	[Nm]	54 - 217
Nominal torque on output shaft:	T_{2Nzul}	[Nm]	40 - 150
Max. backlash:	j	[arcmin]	2 - 5
Max. input speed:	$N_{1maxzul}$	[min ⁻¹]	6500 - 7500

The operating mode is S5. Please contact us if you intend to use other operating modes.

[Catalogues and maintenance instructions](#)

[2D and 3D data](#)

[Inquiry form](#)

Do you have individual requirements?

We have the right customer-specific solution for you. We look forward to hearing from you.

[Customized solution](#)



SKPR

Angular gearbox with solid shaft without key

Ratios:	i	[-]	12,0 - 100,0
Max. acceleration torque:	$T_{2\text{maxzul}}$	[Nm]	100 - 950
Nominal torque on output shaft:	$T_{2\text{Nzul}}$	[Nm]	70 - 550
Max. backlash:	j	[arcmin]	3 - 5
Max. input speed:	$N_{1\text{maxzul}}$	[min ⁻¹]	6500 - 7500

The operating mode is S5. Please contact us if you intend to use other operating modes.

[Catalogues and maintenance instructions](#)

[2D and 3D data](#)

[Inquiry form](#)

Do you have individual requirements?

We have the right customer-specific solution for you. We look forward to hearing from you.

[Customized solution](#)



SKPG

Angular gearbox with flanged shaft

Ratios:	i	[-]	12,0 - 100,0
Max. acceleration torque:	$T_{2\text{maxzul}}$	[Nm]	100 - 950
Nominal torque on output shaft:	$T_{2\text{Nzul}}$	[Nm]	70 - 550
Max. backlash:	j	[arcmin]	3 - 5
Max. input speed:	$N_{1\text{maxzul}}$	[min ⁻¹]	6500 - 7500

The operating mode is S5. Please contact us if you intend to use other operating modes.

[Catalogues and maintenance instructions](#)

[2D and 3D data](#)

[Inquiry form](#)

Do you have individual requirements?

We have the right customer-specific solution for you. We look forward to hearing from you.

[Customized solution](#)